Appl. No. 10/085,175
Amdt. Dated August 26, 2004
RCE Reply to Office Action Final Rejection July 15, 2004
Revised Claims per December 7, 2004 Office Communication Supplemental 12/17/04

## Claims

- 1. (currently amended): A <u>self</u> pressurized, <u>by fluid thermal expansion or phase change</u> (<u>water to steam</u>), <u>fluid filled closed</u> loop solar <u>eollector</u> <u>collection</u> system for delivering solar energy from a roof mounted <u>collector</u> panel to a <del>domestie</del> hot water tank including: a pressurization system capable of maintaining system pressures above atmospheric pressure to increase the boiling point of the heat transfer fluid; a <u>pressurized</u> fluid radiator/overflow/recovery apparatus to catch overflow heat transfer fluid and trapped air and return the fluid to the system <u>by vacuum</u> while keeping air out; a heat transfer fluid to air <u>pressurized</u> radiator <u>and</u> or solar collector <u>pressure activated</u> air <u>vents dampers</u> to prevent the solar collectors from overheating during no flow conditions; an <u>a water based</u> antifreeze heat transfer fluid to prevent damage from freezing in winter environments; a flexible umbilical to connect solar collector and water tank heat exchanger together; a circulation pump; control system and an <u>double walled</u> internal heat exchanger which is adaptable to <u>existing the</u> hot water tank, to deliver heat from the heat transfer fluid to the hot water tank.
- 2. (currently amended): A boiling activated <u>pressurized</u> radiator solar collector overtemperature protection system, which includes a <u>pressurized</u> fluid <u>to air</u> radiator/overflow/recovery apparatus to catch overflow heat transfer fluid and trapped air and return the fluid to the system <u>using vacuum</u> while keeping air out, utilizes no moving actuators, and includes a boiling gas/liquid separator, which allows steam <del>to reach a condensed in the pressurized</del> liquid to air radiator <del>and allows the condensed water</del> to be returned to kept in the pressurized fluid loop, so the sun's heat energy is dissipated to the ambient air flowing over the pressurized radiator and when the collector boiling stops, the sun's heat energy is delivered to the circulating heat transfer fluid and then to the hot water tank fluid loop.

BB98/120 2 of 4

Appl. No. 10/085,175

Amdt. Dated August 26, 2004

RCE Reply to Office Action Final Rejection July 15, 2004

Revised Claims per December 7, 2004 Office Communication Supplemental 12/17/04

3. (currently amended): A pressure activated solar collector over-temperature protection system which utilizes solar collector air dampers as moving parts, including: a <u>steam</u> pressure activated mechanical actuator, which opens before the systems' regulated pressure is reached; and a set of damper valves, which control airflow over the solar collector panel, so when opened the sun's <u>heat</u> energy is dissipated to the flowing ambient air and <u>then</u> when <u>the dampers are</u> closed the sun's <u>heat</u> energy is delivered to the circulating heat <u>transfer</u> fluid <del>loop</del> and <u>thus to the</u> hot water tank.

## 4. (cancelled):

- 5. (currently amended): The system according to as in claim 1 comprised of a with a 220/115 VAC controller and pump and boiling activated over-temperature protection according to claim 2.
- 6. (currently amended): The system as in claim 1 comprised of a The system according to claim 1, with a 220/115 VAC controller and pump, with pressure activated overtemperature protection according to claim 3.
- 7. (currently amended): The system as in claim 1 comprised of a The system according to claim 1, with a photovoltaic panel and low voltage (12VDC) pump, with boiling activated over-temperature protection according to claim 2.
- 8. (currently amended): The <u>system as in claim 1 comprised of a</u> The <u>system according</u> to claim 1, with a photovoltaic panel and low voltage (12VDC) pump, with pressure activated over-temperature protection according to claim 3.
- 9. (new) The system as in claim 2 comprised of a 220/115 VAC controller and pump and boiling activated over-temperature protection.

3 of 4

11.00

Appl. No. 10/085,175

Amdt. Dated August 26, 2004

RCE Reply to Office Action Final Rejection July 15, 2004

Revised Claims per December 7, 2004 Office Communication Supplemental 12/17/04

10. (new) The system as in claim 3 comprised of a 220/115 VAC controller and pump, with pressure activated over-temperature protection.

- 11. (new) The system as in claim 2 comprised of a photovoltaic panel and low voltage (12VDC) pump, with boiling activated over-temperature protection.
- 12. (new) The system as in claim 3 comprised of a photovoltaic panel and low voltage (12VDC) pump, with pressure activated over-temperature protection.